

SHARPENING WELDING FILTRATION CLEANING CONSUMABLES CATALOG NEWS STORE

# ELITE LAVAmaq 780

Cleaning, drying and corrosion protection in a single process

Complete cleaning of the tools with automatic drying

Maximum Load: 150 Kg.

Máx. 1 stack of intermediate size saw blades



The Elite LAVAmaq 780 provides a tool cleaning system that will save you a lot of operator time. Insert dirty tools such as circular saws, blades or milling cutters into the machine and within 10 to 15 minutes they will be completely clean, dry and protected against corrosion.

The cleaned tool is ready to be introduced into the grinder without contaminating the coolant.

It allows to clean saws and tools up to a diameter of 750 mm.

You can also insert the already sharpened tools for 1 minute so that they receive a corrosion protection that is completely dry and unnoticed.



Loading of tools



Circular saw blades cleaned

### Optional accesories

- Automatic rotation for LAVAmaq 780 tray. Necessary with high resistance dirt as resins.
- Inox steel tray for LAVAmaq 780
- Vapor exhaust
- Automatic filler for the tank
- Automatic drain of the tank
- Automatic oil separator
- Grid for the placement of discs

## **SPECIFICATIONS**

110 l/min and 2,2 bar

#### Technical data

Pump

**Maximum tool dimensions** ø750×500 mm. (Diameter x Height)

Maximum tool weight 150 kg

Cleaning temperature up to 60°C

Water tank capacity 120 liters

**Connection** 400V or 220V 3 Ph. 50/60 Hz.

#### Available versions

Model Net size Packing weight

LAVAmaq 780 1200 x 1050 x 1130 mm. 80 Kg.

#### HIGHLIGHTS

- Machine made of high quality stainless steel plate with 2 mm. thickness
- Adjustable water heating temperature up to 60°C
- Programmable timer from 1 to 30 minutes of the washing cycle
- Biodegradable detergent with tool corrosion protection
- Motorization of the tool carriage available as an option
- Draining system for quick and easy change of the liquid

We reserve the right to make design changes in the interest of technical progress.